

Leak Sealer F4 500ml

56603

Ideal for reducing pressure loss from sealed systems

Seeks out and seals inaccessible, internal microscopic leaks fast

Saves time and money on draining down the system and repair costs

Safe to use - does not cause blockages in pipework or vulnerable boiler components such as pumps, air vents and heat exchangers

Designed to be left permanently in the system - compatible with all metals and materials, including aluminium

One 500ml recyclable bottle treats up to 130 litres of system water (16 radiators) and the equivalent of 250m² of underfloor systems.



Leak Sealer F4 is a internal leak sealer developed for use throughout a central heating system to seal small, inaccessible leaks and weeps which may cause pressure loss and boiler breakdown. Once dispersed within the system, the product finds the area of oxygen ingress and forms a polymer to seal the pinhole. Effective within 1-24 hours after application, the unique sealing efficiency of this market-leading water treatment chemical has been proven to prevent blockages or restrictions within the boiler or vulnerable system components such as pumps and safety devices. A leak can be quickly and efficiently sealed, without the need for a complete system drain down.

Application

The recommended use concentration of the product is 0.385%. One single dose of this product treats a larger sized property with a heating system of 130 litres, up to 16 radiators or 250 sqm of underfloor heating. For open vented systems add via the feed and expansion tank. For sealed systems add via a suitable dosing point (e.g. a towel rail or an in-line system filter). Alternatively, use a suitable dosing vessel to inject the product into the system. In single feed indirect cylinders, e.g. 'Primatic' or similar, potable water chemicals must be used.

Package, Handling & Safety

Fernox Leak Sealer F4 is supplied in 500 ml bottles.

Fernox Leak Sealer F4 is classified as non-hazardous, but as with all chemicals, keep out of reach of children. In case of contact with eyes or skin, rinse immediately with plenty of water.

Specification

Fernox Leak Sealer F4 is a polymer emulsion.

Colour: Off white

Odour: Faint

Form: Viscous liquid
pH (conc.): 5.0 - 7.0
pH (in-use): 7.0 - 8.5
SG: 1.0 at 20°C

Single Item

Height mm	182
Width mm	88
Depth mm	52
Weight kg	0.600
Barcode EAN	5014551566033

Outer Carton

Outer Height mm	195
Outer Width mm	265
Outer Depth mm	180
Outer Weight kg	6.130
OCU Bar Code No. ITG	5014551000766
Transit Type	CP1 1200 x 1000

Last modification 11-01-2021 (d/m/y)